

Easy-On

# TBK-MD6921



## MAIN FEATURES

- 2MP Fixed Turret Camera
- Metal Plastic Housing
- Up to 1920x1080@30fps
- S+265/H.265/H.264
- Min. illumination Color: 0.02Lux@F2
- Smart IR, IR Range: 30m
- Built-in Mic
- Operating Conditions -30°~60°, 0~95% RH
- POE

TBK Live Client:  
Software escritorio



TBK VMS:  
App móvil



iOS



Android


**TBK-MD6921**
**SPECIFICATIONS**

<b>Camera</b>	
<b>Image Sensor</b>	1/2.9"CMOS
<b>Min. Illuminación</b>	Color:0.02Lux@(F2.0,AGC ON),B/W:0Lux with IR
<b>Shutter Time</b>	1s-1/100000s
<b>Day&amp;Night</b>	IR-cut filter with auto switch (ICR)
<b>WDR</b>	DWDR
<b>S/N</b>	>37dB
<b>Angle Adjustment</b>	0-340°;0-75°;0-360°
<b>Lens</b>	
<b>Lens Type</b>	Fixed
<b>Focal Length</b>	2.8mm
<b>Lens Mount</b>	M12
<b>Aperture Range</b>	F2.0,Fixed
<b>Field of View</b>	102.8°(H);57.6°(V);117.8°(D)
<b>DORI Distance</b>	Detect:40.0m Observe:15.9m Recognize:8.0m Identify:4.0m
<b>Illuminator</b>	
<b>IR LEDs</b>	2
<b>IR Distance</b>	30m
<b>Wavelength</b>	850nm
<b>White LEDs</b>	N/A
<b>Whitelight Distance</b>	N/A
<b>Compression Standard</b>	
<b>Video Compression</b>	S+265/H.265/H.264B/H.264M/H.264H
<b>Video Bit Rate</b>	32k-4Mbps
<b>Audio Compression</b>	G.711A/G.711U
<b>Audio Sampling Rate</b>	8kHz


**TBK-MD6921**
**SPECIFICATIONS**

<b>Image</b>	
<b>Max. Resolución</b>	1920x1080@30fps
<b>Main Stream</b>	PAL: 25fps(1920x1080,1280x720,704x576,640x480) NTSC: 30fps(1920x1080,1280x720,704x480,640x480)
<b>Sub Stream</b>	PAL:25fps(704x576,704x288,352x288,640x360) NTSC:30fps(704x480,704x240,352x240,640x360)
<b>Third Stream</b>	N/A
<b>BLC</b>	Yes
<b>HLC</b>	Yes
<b>AGC</b>	Yes
<b>3D DNR</b>	Yes
<b>White Balance</b>	Auto/Semi-auto/Manual/Sunny/Natural light/Warm light/Sodium lamp/ Incandescent lamp/Locked white balance
<b>ROI</b>	N/A
<b>Corridor mode</b>	N/A
<b>EIS</b>	N/A
<b>OSD</b>	1region;16*16/32*32/48*48
<b>Picture Overlay</b>	N/A
<b>Privacy Mask</b>	4 regions
<b>Defog</b>	Yes
<b>Feature</b>	
<b>Alarm Trigger</b>	Motion Detection; IP Address Conflict
<b>Linkage Method</b>	trigger capture
<b>Video Analytics</b>	N/A
<b>Rules of behavior analyse in 1 scene</b>	N/A
<b>Early Warning(EW)</b>	N/A
<b>Auto -Tracking</b>	N/A
<b>Face Mode</b>	N/A
<b>Face Detection Performance</b>	N/A


**TBK-MD6921**
**SPECIFICATIONS**

<b>Network</b>	
<b>ANR</b>	N/A
<b>Protocols</b>	HTTP;TCP/IP;UDP;ICMP;DHCP;DNS;NTP;IPv4;Telnet;Unicast
<b>System Compatibility</b>	onvif Profile S/ T;CGI;MILSTONE
<b>Remote Connection</b>	≤2
<b>Client</b>	TBK Live Client
<b>Moblie Client</b>	TBK VMS
<b>Web</b>	IE10+;Firefox52+;Edge89+;Safari11+;Chrome57+
<b>Interface</b>	
<b>Communication Interface</b>	1 RJ45 10M/ 100M self adaptive Ethernet port
<b>Audio I/O</b>	N/A
<b>Alarm I/O</b>	N/A
<b>Built-In Mic</b>	Yes
<b>Built-In Speaker</b>	N/A
<b>Reset Button</b>	N/A
<b>On-board storage</b>	N/A
<b>Additional interfaces</b>	N/A
<b>General</b>	
<b>Web Client Language</b>	Spanish/English
<b>Operating Temperature</b>	-30°C - 60°C
<b>Operating Humidity</b>	0-95%
<b>Storage Temperature</b>	-30°C - 60°C
<b>Storage Humidity</b>	0-95%(non-condensing)
<b>Power Supply</b>	POE 802.3af,MAX 6W
<b>Protection</b>	Surge protection 2000V;Lightning proof 6000V;IP67
<b>Boundary Dimensions</b>	117(L)117(W)96(H)mm
<b>Package Dimensions</b>	140(L)140(W)120(H)mm
<b>GrossWeight</b>	0.34kg
<b>NetWeight</b>	0.24kg



TBK-MD6921

SPECIFICATIONS

DIMENSIONS (Unit:mm)

