


DATASHEET

TBK-BUL4935

MAIN FEATURES

- HD 4 in 1.
- Ultrastarlight, full time color mode.
- 1080P resolution.
- 3.6mm fix lens.
- Sensitivity: 0,0005 Lux color (F1.0, AGC ON).
- Wide Dynamic Range 130 dB.
- 20 m white light illumination range.
- IP67.

Ultrastarlight bullet camera, with full time color mode. With a sensitivity of 0,0005 Lux color, and with double-scan Wide Dynamic Range (130 dB), it provides a clear and colorful video in dark environments, even with strong backlighting.





TBK-BUL4935
SPECIFICATIONS

CAMERA	
Image Sensor	2 MP CMOS image sensor
Resolution	1920 (H) × 1080 (V)
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Min. illumination	Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Slow Shutter	Max. 16x
Lens	3.6 mm fixed lens
Horizontal Field of View	83.6° (3.6 mm)
Lens Mount	M16
Day & Night	Color
Angle Adjustment	Pan: 0° to 360°; Tilt: 0° to 180°; Rotate: 0° to 360°
Synchronization	Internal synchronization
WDR (Wide Dynamic Range)	130 dB
MENU	
AGC	Yes
White Balance	Auto/Manual
HLC	Yes
BLC (Backlight Compensation)	Yes
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable areas
WDR	Yes
Functions	Brightness, Sharpness, 3D DNR, Mirror, Smart light
INTERFACE	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
GENERAL	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±25%
Power Consumption	Max. 3 W
Protection Level	IP67
Material	Metal
White Light	Up to 20 m
Communication	Up the coax (TVI output)
Dimensions	181.4 mm × 70 mm × 68 mm (7.14" × 2.75" × 2.68")
Weight	Approx. 390 g (0.86 lb.)



TBK-BUL4935

DIMENSIONS



ACCESSORIES



TBK-364C
Junction box

